ASSE International Product (Seal) Listing Program

ASSE 1019-2011(R2016)

Performance Requirements for Wall Hydrant with Backflow Protection and Freeze Resistance

Manufacturer:					
	E-mail: E-mail: Laboratory File Number:				
Address:					
Model # Tested:					
Additional models report applies to:					
Additional Model Information (i.e. orientation, series, end connections, shut-off valves)					
Date models received by laboratory:	Date testing began:				
Date testing was completed					
If models were damaged during shipment, describe damages:					
Prototype or production sample?					
Were all tests performed at the selecte	d laboratory? ○ Yes ○ No				

General information and instructions for the testing engineer:

The results within this report apply only to the models listed above.

There may be items for which the judgment of the test engineer will be involved. Should there be a question of compliance with that provision of the standard, a conference with the manufacturer should be arranged to enable a satisfactory solution of the question.

Should disagreement persist and compliance remain in question by the test agency, the agency shall, if the product is in compliance with all other requirements of the standard, file a complete report on the questionable items together with the test report, for evaluation by the ASSE Seal Control Board. The Seal Control Board will then review and rule on the question of compliance with the intent of the standard then involved.

Documentation of material compliance must be furnished by the manufacturer. The manufacturer shall furnish to the testing agency, a bill of material which clearly identifies the material of each part included in the product construction. This identification must include any standards which relate thereto.

Section III

3.0	Perfor	Performance Requirements and Compliance Testing			
3.1	Hydrostatic Pressure Tests				
	3.1.2	Procedure What pressure the test pressure? psi (kPa) What was the water temperature used for this test? °F (°C) How long was the pressure held for? minutes			
	3.1.3	Criteria Was there any indication of damage or external leakage? O Yes O No O Questionable If yes or questionable, explain Is the device in compliance with this section?			
		O Yes O No O Questionable If no or questionable, explain			
3.3	Deterioration at Maximum Rated Temperature and Pressure				
	3.3.2	Procedure What was the flow rate used for this test? GPM (L/min) What was the water temperature used for this test? °F (°C) What was the pressure used for this test? psi (kPa) What was the duration of the test? hours/day for days OR continuous hours			
3.6	Self-Draining Capabilities				
	3.6.2	Procedure			
		What type is the device? O Type "A" O "Type B" O Type "C" What was the water pressure used for this test? psi (kPa) What was the water temperature used for this test? °F (°C) What was the temperature inside the cold chamber while running the test? °F (°C) What was the time required to lower the device to 0.0°F (-17.8°C)? minutes			
	3.6.3	Criteria Once the temperature of the device inside the cold chamber was lowered to a maximum of 0.0°F (-17.8°C), was the device able to flow water? O Yes O No O Questionable If no or questionable, explain			
		Is the device in compliance with this section?			
		O Yes O No O Questionable If no or questionable, explain			

3.8	Outlet Pressure Release for Type A and Type B Devices					
	3.8.2	Procedure				
		What was the system pressurized to? psi (kPa)				
		What was the inlet pressure dropped to when the quick acting valve was opened?				
		psi (kPa)				
	3.8.3	Criteria				
		Did the device discharge the hose to 0.0 psi (0.0 kPa)?				
		O Yes O No O Questionable				
		If no or questionable, explain				
		Is the device in compliance with this section?				
		O Yes O No O Questionable				
	If no or questionable, explain					
3.9	Backflo	Backflow Prevention for Type C Devices				
	3.9.2	Procedure				
		What was the system pressurized to? psi (kPa)				
		What was the inlet pressure dropped to when the quick acting valve was opened?				
		psi (kPa)				
		After disconnecting the inlet piping, how long was the device held for? hours				
	3.9.3	Criteria				
		Was there any leakage through the check valve into the inlet of the device?				
		O Yes O No O Questionable				
		If yes or questionable, explain				
		Is the device in compliance with this section?				
		O Yes O No O Questionable				
		If no or questionable, explain				

LISTED LABORATORY:				
ADDRESS:				
PHONE:	FAX:			
TEST ENGINEER(S):				
If applicable:				
OUTSOURCED LABORATORY:				
ADDRESS:				
PHONE:	FAX:			
TEST ENGINEER(S):				
Scope of outsourced testing:				
We certify that the evaluations are based on our best judgments and that the test data recorded is an accurate record of the performance of the device on test.				
Signature of the official of the listed laboratory:Signature				
Title of the official:	Date:			